



Touch Terminal SP-630

Economical and Powerful



When demanding economical POS solution and requiring a powerful terminal for today's ever changing POS environment, the SP-630 is the right answer in view cost efficiency and performance.

To meet those requirements, the new SP-630 is equipped with the Intel Celeron N2807 dual core CPU, which is of course fanless, to guarantee reliability and low maintenance. Memory wise, up to 4GB RAM will be supported.

The elegant body of SP-630 utilizes 5 wire resistive ELO touch technology for reliable operation at Point-of Sales. The monitor is flexible and can be adjusted to meet the requirements of any workplace - whether with convenient VESA / wall mount or wide tilt angle.

There are different possibilities to connect a customer display (VFD 2x20 chr.) or a second monitor e.g. for digital signage purposes. To round up the SP-630 Touch POS system, a wide range of helpful POS peripheral options are available.

Special Features

- Powerful Intel® Celeron N2807 dual core processor
- Supports up to 4GB RAM
- Flexible modular design and dual display support
- Spill and dust resistant front panel, IP65
- Convenient VESA / wall mount and wide tilt angle monitor
- Green low power consumption

Optional

- Customer display module (2 x 20 VFD)
- 2nd monitor (CD-70, PM-116 or PM-15BZ)
- 3-track MSR, Smart Card reader, RFID reader
- Fingerprint sensor, I-Button/Dallas key/Addimat
- LPT port / Audio connector

Touch Terminal SP-630

Technical data

Item	SP-630		
CPU	Intel® Celeron™ N2807, 1.58GHz up to 2.16GHz, dual core, 1MB cache, fanless		
LCD	15" TFT-LCD, resolution 1024 x 768		
Touch	5 wire resistive ELO touch (PS/2 interface)		
RAM	Up to 4GB (DDR3L)		
LAN	Onboard 10/100/1000 BASE-T Gigabit Ethernet		
Storage	Internal 2.5" SATA HDD, SATA SSD (option)		
I/O Interface	external 3x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM3 by jumper) external 3x USB 2.0 external 1x USB 3.0 1x RJ-45 Ethernet 1x RJ-11 Cash drawer control (for 2 cash drawers) 1x Mini PCI-e 1x ext. VGA for 2nd monitor 1x DC+ 12V Out		
Operating System	Windows 7, POSReady7, Windows 8.1, Linux (ubuntu)		
Power Supply	AC100~240V/DC+12V, 7.5A, 90W power adaptor		
Dimensions	360mm (W) x 240mm (D) x 365mm (H)		
Environment	Operating	Storage	
	Temperature	0°C ~ +40°C	-20°C ~ +60°C
	Humidity	15% ~ 80%	15% ~ 80%
Options	Customer display module (2 x 20 VFD), 2nd monitor (CD-70, PM-116 or PM-15BZ), 3-track MSR, Smart Card reader, RFID reader, FingerPrint sensor, I-Button/Dallas key/Addimat, LPT port / Audio connector can be provided as factory option		



15" Touch monitor with 5 wire resistive touch, spill and dust proof front panel, IP65



Flexible and modular design supports customer / dual display options



Compact and small footprint, counter space saving



Wide angle tilt for best operation position